

INFRARED THERMOMETER

Non-contact Measurement "0" Risk of Cross-infection



LFR30B



SAFE



FAST



CONVENIENT

**SAFE**

Non-contact body temperature measurement avoids cross-infection

**FAST**

Imported probe from Germany, temperature displays in 1 second

**CONVENIENT**

Blue dots focusing calibration system help users to find the optimal measuring distance

**COLOR INDICATOR**Three colored backlights indicate the different temperature ranges visually <math><37.5^{\circ}\text{C}</math> Green /

TWO MODES

Two temperature measurement modes: Human body / Object

DATA RECORD

99 sets of data can be stored for tracking the changes of body temperature

POWER SAVING

Auto shut down when there is no operation for 60 seconds

SPECIFICATIONS

| | |
|----------------------------------|---|
| Measuring Position | Forehead |
| Measuring Distance | 0cm~5cm |
| Display | LCD Screen |
| Resolution | 0.1°C |
| Measuring Range | Human Body: 32.0°C ~ 43.0°C Object: 0°C ~ 100°C |
| Accuracy | For body: $\pm 0.3^{\circ}\text{C}$ (34°C~43°C) $\pm 0.4^{\circ}\text{C}$ (32°C~33.9°C) |
| Operating Temperature & Humidity | Temperature: 5°C~40°C Humidity: $\leq 85\%RH$ |
| Storage Temperature & Humidity | Temperature: -20°C~55°C Humidity: $\leq 95\%RH$ |
| Power Supply | 2 X 1.5V AAA batteries |
| Service Life | 5 years |

Lepu Medical Technology (Beijing) Co., Ltd.

Manufacturer: Shenzhen LEPU Intelligent Medical Equipment Co., Ltd.

Address: Building 9, Baiwangxin High-Tech Industrial Park, Songbai Road, Nanshan District, Shenzhen, China

Website: en.lepumedical.com